


FLOOR PLAN

POLYURETHANE FORMED IN PLACE INSULATION
MINIMUM R=14.10

METAL ROOF
METAL PURLINS



METAL SIDING

POLYURETHANE FORMED IN PLACE
INSULATION MINIMUM R=14.50

1"X4" VERTICAL STRIPS SPACED
16" O.C. OR AS REQUIRED FOR OPTIONAL FINISH

2"X4" NAILING GIRTS ATTACHED TO
METAL GIRTS


5" MINIMUM THICK CONCRETE
WHERE FORK LIFT TRUCK TO
OPERATE (5 BAG) MIX MAX. 5 GAL.
WATER PER BAG) 6" X 6" 10/10
W.W.F. REINF.

6 MIL POLYETHYLENE
VAPOR BARRIER

4" CRUSHED STONE MAX
SIZE AGGREGATE 1 1/2

SECTION "A-A"

SCALE:
12' 6" 0" 1' 2' 3' 4'




INSULATION WITH
MINIMUM R= 3.7
SUGGESTED

METAL SIDING
CEMENT
PLASTER ABOVE
GROUND

1" X 12" CONTINUOUS
POLYURETHANE

DETAIL "1'-1"

SCALE:
12' 6" 0" 1' 2' 3' 4'



4" MINIMUM THICK
CONCRETE WHERE
NO VEHICLES USED

6" MIL POLYETHYLENE

4" CRUSHED STONE

6" X 6" 10/10 W.W.F. REINF.

SECTION "B-B"

SCALE:
12' 6" 0" 1' 2' 3' 4'

FOOTER TO BE SPECIFIED BY FRAME MANUFACTURER
TO PROVIDE 30 P.S.F. SNOW LOAD 15 P.S.F. WIND LOAD

12' 0" 2' 4' 8' 12'

1" X 12" CONT.
POLYURETHANE

1" X 4" VERTICAL STRIP

2" X 4" NAILING STRIP

1" X 24" CONTINUOUS
POLYSTYRENE

DETAIL "2'-2"

SCALE:
12' 6" 0" 1' 2' 3' 4'

USE 1" X 24" POLYURETHANE
TO FORM PIER

DETAIL "2'-2"

SCALE:
12' 6" 0" 1' 2' 3' 4'

COOPERATIVE EXTENSION WORK IN
AGRICULTURE AND HOME ECONOMICS

AND
UNITED STATES DEPARTMENT OF AGRICULTURE COOPERATING

APPLE STORAGE & PACKING FACILITY

VPI '69 EX. 6314 SHEET 1 OF 1