



- 1 210-lb asphalt shingles on 3/8" plywood sheathing. Use H-clips at unsupported plywood edges midway between roof trusses 2'-0" o.c.
- 2 metal roofing on 2" x 4" nailers spaced as per roofing manufacturer. Roof trusses 4' o.c.
- 3 insulated ceiling; 6" friction-fit insulation between trusses 4'-0" o.c., 2" x 4" strapping and blocking 4'-0" o.c., 4-mil P.E. vapour barrier, 3/8" plywood, painted finish
- 4 insulated ceiling same as 3 except trusses 2'-0" o.c., 1" x 4" strapping and blocking 2' x 4' o.c., 2" plywood
- 5 2 - 2" x 6" plates
- 6 framing anchor
- 7 plywood baffle
- 8 3/4" x 12" anchor bolts 4' o.c.
- 9 1/2" bolt, truss to post @ 8' o.c. max.
- 10 face board, 2" for trusses 4' o.c., 1" for 2' o.c.
- 11 top of plate
- 12 2" screened inlet
- 13 soffit
- 14 2" x 8" outer plate (notched into post)
- 15 2" x 6" and 2" x 8" plates
- 16 blocking ripped from 2" x 6"
- 17 exterior siding, 15 lb asphalt felt, (breather type) 2" x 6" studs @ 2'-0" o.c., 4" friction fit insulation, 4-mil P.E. vapour barrier, 3/8" plywood painted as req'd. by local regulations.
- 18 exterior siding, 15 lb asphalt felt, (breather type), 2" x 6" girts @ 2'-0" o.c., 4" friction fit insulation, 4-mil P.E. vapour barrier. 3/8" plywood painted as req'd. by local regulations. block at joints
- 19 2" x 6" bottom girt, pressure treated
- 20 pre-paint plywood, caulk between plywood and treated planking. Then nail through planking and plywood with 3 1/2" galv. nails (rabbit plank to fit plywood and bevel)
- 21 3/16" high-density recompressed exterior type asbestos board, drill for galv. nails
- 22 gravel splash pad at grade
- 23 2" rigid insulation expanded polystyrene
- 24 4" concrete floor, 6 mil P.E. moisture barrier, compacted sand or gravel fill
- 25 2" x 6" pressure treated planking, stagger end joints at posts
- 26 4" x 6" pressure treated wood post @ 8'-0" o.c. max.
- 27 18" dia. x 8" concrete pad
- 28 stud wall option
- 29 post frame option

SYN	REVISIONS	CHECKED	DATE	APPROVED

CANADA FARM BUILDING PLAN SERVICE

WALL SECTIONS		DESIGNED <i>R.J.M.</i>	DATE MAY/71	PLAN
		DRAWN <i>[Signature]</i>	REVISED	2125
		TRACED	SCALE	SHEET 3 OF 5
		CHECKED <i>H.A.J.</i>	NO SCALE	

A Detail No.
 B Sheet No. On Which Detail Originates
 C Sheet No. On Which Detail is Shown